



SBM Belt Conveyor



What we do today is to ensure the future of our
group with youth and spirit forever and ever.

- SBM

Belt Conveyor



Belt Conveyor Overview

Belt Conveyor is the essential and economical transferring set in the uninterrupted production line. In terms of transferring capacity, belt conveyor can be classified into two types, the heavy type such as for mining convey and the light type for plastic, food and chemical industry, etc. Belt conveyor features with strong transferring capacity, easy maintenance and long conveying distance. SBM is a professional belt conveyor manufacturer, according to different material, we design different belt conveyor. Our belt conveyor is your best choice.

Applications

Belt Conveyor is widely used in the fields such as mining, metallurgical and coal industry to transfer sandy or lump materials. Single set or unit of multi-sets of belt conveyor can be chosen to meet various production lines.

Main Features and Benefits

1. Stable and longer convey with no relative movement.
2. Noise reduction.
3. Simple structure, easy maintenance, energy-saving and low cost.

Technical Data

Belt Width(mm)	Belt Length (m) /Power (Kw)			Belt Speed(m/s)	Capacity(t/h)
400	≤12/1.5	12↔20/2.2↔4	20↔25/3.5↔7.5	1.3↔1.6	40↔80
500	≤12/3	12↔20/4↔5.5	20↔30/ 5.5↔7.5	1.3↔1.6	40↔80
650	≤12/4	12↔20/5.5	20↔30/7.5↔11	1.3↔1.6	131↔323
800	≤6/4	6↔15/5.5	15↔30/7.5↔15	1.3↔1.6	278↔546
1000	≤10/5.5	10↔20/7.5↔11	20↔40/11↔12	1.3↔2.0	435↔853
1200	≤10/7.5	10↔20/11	20↔40/15↔30	1.3↔2.0	655↔1284

Belt conveyor working environment



The conveyers which are produced by SBM consist of standard parts, which are advanced and simple in structure, easy to maintain. They are widely used in mining, metallurgical and coal industry to transfer sandy or lump material, or packaged material. According to different transferring equipment, the transfer system can be one independently or multi-conveyers or combined with other transfer equipments. The belt conveyor can be installed horizontally or aslope to meet the needs of different transfer lines.

The belt conveyers produced by SBM can be operated in the circumstance temperature range from -20 to +40. The temperature of transferred material by this belt conveyor should be lower than 50.

Sales Hot-Line

International Dept.1: Tel: 0086-21-58383098

International Dept.2: Tel: 0086-21-58383028

International Dept.3: Tel: 0086-21-58383058

International Dept.4: Tel: 0086-21-58383003

International Dept.5: Tel: 0086-21-58383022

E-mail & Fax

E-mail: sbm@unisbm.com

Fax: 0086-21-58383058

Office Address & Zip

Add : No.416 Jianye Road, South Jinqiao Area, Pudong, Shanghai, China

Zip / Postal Code : 201201